



PLATINUM PRO™ AF-6500 FLOOR FINISH

Urethane enhanced Platinum Pro™ AF-6500 Floor Finish is the ultimate protection against ESD events.

Flooring applied with Platinum Pro™ AF-6500 has ESD protection, safety, gloss, and are easy to maintain.

Using the longest lasting and highest performance available, Platinum Pro™ AF-6800 immediately reduces the cost of maintenance and increases ESD protection.



Benefits

Static Dissipative	Protects devices from damage and workers from explosion/shock
Low VOC	Regulatory conformance/personnel safety
High Abrasion	Long lasting, reduces repetitive application
High Gloss	Aesthetically appealing "wet look"
Low Tribogeneration	Eliminates damage to devices
UL Listed	Slip resistant
No Formaldehyde/ Phthalates	Safe to use
No Alkalis/Acids	Safe to use
Water Based	Biodegradable/non-flammable/low odor



FLOOR COATING AND FINISHING MATERIAL CLASSIFIED BY UNDERWRITERS LABORATORIES, INC.® AS TO SLIP RESISTANCE ONLY

Static Solutions, Inc.

Safety Information

Does not contain:

Glycol Ether DE	CAS# 111-90-0
Formaldehyde	CAS#50-00-0
Dibutyl Phthalate	CAS#87074-2

Health	1
Flammability	0
Reactivity	0
Personal Protection	B

Warranty: Static Solutions, Inc. expressly warrants that for a period of (1) one year from the date of purchase any Static Solutions, Inc. product will be free of defects in materials and will function within its specifications. Within the warranty period, the product will be repaired or replaced at Static Solutions, Inc.'s option with no cost to the customer as long as Static Solutions, Inc. receives notice during the warranty period. Defective products must be shipped prepaid to Static Solutions, Inc.'s factory. Call Static Solutions, Inc.'s customer service at 508-480-0700 for a return authorization number. Include a copy of the invoice, packing slip, or other proof of purchase.

Warranty Exclusion: The foregoing express warranty is made in lieu of other product warranties express and implied, including merchantability and fitness for a particular purpose which are specifically or indirectly disclaimed. The express warranty will not apply to defects or damage due to neglect, misuse, accidents, alterations, operator error, failure to properly maintain, follow instruction, or failure to clean or repair products.

Limit of Warranty: In no event will Static Solutions, Inc. or seller be responsible or liable for special, incidental or consequential losses or damages, whether based on tort, contract, or the use of or inability to use, the product. Before using the product users shall determine the suitability of the product for their intended use. The users assume all risk and liability whatsoever in connection therewith. Fulfillment of Static Solutions, Inc.'s warranty obligations will be the customer's exclusive remedy and Static Solutions, Inc. and seller's limit of liability for any breach of warranty or otherwise.

For additional OHM-SHIELD™ product literature, call or fax the Static Solutions, Inc. sales department.

Static Solutions, Inc.

331 Boston Post Road - East
Marlborough, MA 01752, USA
Tel: 508.480.0700
Fax: 508.485.3353

Static Solutions, Inc. only sells through distributors.
Please call us at 508.480.0700

or log on to our website, www.staticsolutions.com,
or www.staticsolutions.co.uk to find your local distributor.

Specifications

Active Ingredients	Proprietary
Surface Resistance (RTT) ANSI/ESD S7.1-1994	10 ⁷ -10 ⁹ Ohms@100 Volts
Slip Resistance ASTM D2047-5	0.5 Minimum (UL Listed)
Electrostatic Decay Time EIA 5410	0.1 Seconds
% Solids	20% +/- 0.5%
pH	8.0-9.0
Free Ammonia	None
Free Alkali	None
Free Acid	None
Phosphates	None
Color	Milky White
Odor	Mild
Water Solubility	100%
Freeze/Thaw Stability	3 Cycles
Shelf Life	1 Year
Flash Point	None
Weight/Gallon	8.6 lbs./gallon
Biodegradable	Yes
VOC	3.5%

DISTRIBUTED BY: